BOPP UTILITY FILAMENT TAPE

FT70 was designed for light bundling and strapping applications requiring lower tensile strength. Most bundling applications are holding or stabilizing a load and in many general-purpose applications, 90-100lb tensile filament tape is over specified. In many cases 90-100lb tensile products are typically wrapped around a bundle two or more times by the user. In these cases FT70 is ideal, offering a cost savings over higher tensile bundling tape.

FEATURES & BENEFITS

- Hand breakable construction
- No application equipment or knives required
- Readable graphics through contact clear construction











PRODUCT ATTRIBUTES

CHARACTERISTICS		FT70
Color		Clear
Backing		1.0 mil (25µ) biaxially oriented polypropylene film
Adhesive		Synthetic rubber/resin
Reinforcement		Fiberglass
Adhesion to Steel (oz/in of width) (at 90° peel angle)		49 (13.4 N/25mm)
Quick Start	To Kraft	1.7 (0.5 N/25mm)
	To Steel	25 (6.8 N/25mm)
Tensile Strength (lb/in of width)		68 (298 N/25mm)
Elongation (% at break)		3.2
Total Thickness (mils)		3.4 (0.086mm)

PRODUCT APPLICATIONS

- Light bundling, strapping and palletizing
- Load stabilization

MARKETS

- General manufacturing
- Warehouse
- Distribution centers







