

i tape



530

UTILITY GRADE FLATBACK TAPE

An aggressive pressure-sensitive flatback specifically designed to offer a strong, secure seal on a wide variety of substrates. 530 performs well under a wide range of temperatures and humidity conditions. This product is not repulpable.

MADE WITH 60% RENEWABLE RAW MATERIALS!

FEATURES & BENEFITS

- Now made with 2X the adhesion to backing strength for a positive seal in shingling applications
- Aggressive pressure-sensitive adhesive that was specifically designed to stick to a variety of substrates
- Lower unwinds for ease of application
- Cradle to Cradle Certified® Bronze



888-898-7834 | itape.com



PRODUCT ATTRIBUTES

PRODUCT	530
BACKING	Kraft flatback
ADHESIVE	Solvent Cast Natural/ Synthetic Rubber
THICKNESS	7.3 mils
TENSILE STRENGTH	42 lbs/in
ADHESION TO STEEL	50 oz/in
OPERATING TEMPERATURES	+40°F ~ +175°F (+4.4°C ~ +79°C)
COLOR	Brown

PRODUCT INFORMATION

PRODUCT CODE	METRIC SIZE	IMPERIAL SIZE	ROLLS/CASE
81400	48mm x 54.8m	1.88" x 60yd	24
84459	72mm x 54.8m	2.83" x 60yd	16
82873	96mm x 54.8m	3.77" x 60yd	12

PRODUCT APPLICATIONS

- Carton sealing
- Packaging
- Silk screening
- Picture framing
- Beaming/leasing
- Splicing
- Tapping

MARKETS

- Building and Construction
- Electrical
- Moving and Storage
- General Manufacturing
- E-commerce
- Transportation



Scan for more info or visit itape.com/flatback

