

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: 333 Stencil Filler

Product Code: A5863A

Synonyms: Water Based Stencil Filler

1.2. Intended Use of the Product

Use of the Substance/Mixture: Promote adhesion of stencil to substrates. For professional use only.

1.3. Name, Address, and Telephone of the Responsible Party

Company

Intertape Polymer Group

100 Paramount Drive, Suite 300

Sarasota, FL 34232

T: 941-727-5788

1.4. Emergency Telephone Number

Emergency Number : (800) 424-9300 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

Resp. Sens. 1 H334

Skin Sens. 1 H317

Aquatic Acute 2 H401

Full text of hazard classes and H-statements : see section 16

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



GHS08

Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H317 - May cause an allergic skin reaction.

H334 - May cause an allergy or asthma symptoms or breathing difficulties if inhaled.

H401 - Toxic to aquatic life.

Precautionary Statements (GHS-US)

: P261 - Avoid breathing vapors, mist, or spray.

P272 - Contaminated work clothing must not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing, and eye protection.

P284 - [In case of inadequate ventilation] wear respiratory protection.

P302+P352 - If on skin: Wash with plenty of water.

P304+P341 - If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.

P321 - Specific treatment (see section 4 on this SDS).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P342+P311 - If experiencing respiratory symptoms: Call a poison center or doctor.

P363 - Wash contaminated clothing before reuse.

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions. As supplied, this product is a liquid. However, when cured and dried this product may produce combustible dust when cut, sanded, ground, or otherwise processed. Use caution when working with combustible dusts. Use appropriate engineering controls to keep generation of airborne dust to a minimum.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

333 Stencil Filler

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	%	GHS-US classification
Rubber, natural	(CAS-No.) 9006-04-6	15.84	Resp. Sens. 1, H334 Skin Sens. 1, H317 Comb. Dust
Ammonium hydroxide	(CAS-No.) 1336-21-6	< 0.224	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400
Thiram	(CAS-No.) 137-26-8	< 0.0129	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Comb. Dust
1-Dodecanol	(CAS-No.) 112-53-8	0.0012 - 0.012	Eye Irrit. 2A, H319 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Ammonia	(CAS-No.) 7664-41-7	< 0.0013	Flam. Gas 2, H221 Press. Gas (Comp.), H280 Acute Tox. 3 (Inhalation:gas), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 2, H411

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid Measures After Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

First-aid Measures After Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation/rash develops or persists.

First-aid Measures After Eye Contact: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for at least 15 minutes. Obtain medical attention.

First-aid Measures After Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

Symptoms/Injuries: May cause allergy or asthma symptoms or breathing difficulties if inhaled. Skin sensitization.

Symptoms/Injuries After Inhalation: Exposure may produce cough, mucous secretions, shortness of breath, chest tightness or other symptoms indicative of an allergic/sensitization reaction.

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: None known.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

333 Stencil Filler

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, or dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive. Product is not explosive as supplied. However, when cured and dried this product may produce explosive combustible dust when cut, sanded, ground, or otherwise processed.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Acrid smoke and irritating fumes. Sulfur oxides. Carbon disulfide.

Other Information: Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not breathe vapor, mist or spray. Do not get in eyes, on skin, or on clothing.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: As supplied, this product is a liquid. However, when dried this product may produce combustible dust when processed. Use caution when working with combustible dusts. Use appropriate engineering controls to keep generation of airborne dust to a minimum.

Precautions for Safe Handling: Avoid prolonged contact with eyes, skin and clothing. Avoid breathing vapors, mist, spray. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

Promote adhesion of stencil to substrates. For professional use only.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

333 Stencil Filler

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Rubber, natural (9006-04-6)		
USA ACGIH	ACGIH TWA (mg/m ³)	0.0001 mg/m ³ (inhalable particulate matter)
USA ACGIH	ACGIH chemical category	dermal sensitizer, Skin - potential significant contribution to overall exposure by the cutaneous route

Ammonia (7664-41-7)		
USA ACGIH	ACGIH TWA (ppm)	25 ppm
USA ACGIH	ACGIH STEL (ppm)	35 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	18 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	25 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	27 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	35 ppm
USA IDLH	US IDLH (ppm)	300 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	35 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm

Thiram (137-26-8)		
USA ACGIH	ACGIH TWA (mg/m ³)	0.05 mg/m ³ (inhalable fraction and vapor)
USA ACGIH	ACGIH chemical category	dermal sensitizer, Not Classifiable as a Human Carcinogen
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³
USA IDLH	US IDLH (mg/m ³)	100 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³


8.2. Exposure Controls

Appropriate Engineering Controls

: Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing

: Chemically resistant materials and fabrics.

Hand Protection

: Wear protective gloves.

Eye and Face Protection

: Chemical safety goggles.

Skin and Body Protection

: Wear suitable protective clothing.

Respiratory Protection

: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information

: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Milky white
Odor	: Ammonia odor
Odor Threshold	: No data available
pH	: 8 - 9
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: 100 °C (212 °F)
Flash Point	: > 105 °C (221 °F)
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: Not applicable

333 Stencil Filler

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Vapor Pressure	: No data available
Relative Vapor Density at 20°C	: No data available
Relative Density	: No data available
Specific Gravity	: 1
Solubility	: Water: 100 %
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: 150 - 300 cP

9.2. Other Information No additional information available

SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials.
- 10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- 10.6. Hazardous Decomposition Products:** Carbon oxides (CO, CO₂). Acrid smoke and irritating fumes. Hydrocarbons. Nitrogen oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects

Acute Toxicity: Not classified

1-Dodecanol (112-53-8)	
LD50 Oral Rat	> 12800 mg/kg
Ammonium hydroxide (1336-21-6)	
LD50 Oral Rat	350 mg/kg
Ammonia (7664-41-7)	
LD50 Oral Rat	350 mg/kg
LC50 Inhalation Rat	5.1 mg/l (Exposure time: 1 h)
LC50 Inhalation Rat	2000 ppm/4h (Exposure time: 4 h)
Thiram (137-26-8)	
LD50 Oral Rat	1080 mg/kg
LD50 Dermal Rabbit	> 7940 mg/kg
LC50 Inhalation Rat	4.42 mg/l/4h (Species: Sprague-Dawley)

Skin Corrosion/Irritation: Not classified

pH: 8 - 9

Serious Eye Damage/Irritation: Not classified

pH: 8 - 9

Respiratory or Skin Sensitization: May cause an allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Thiram (137-26-8)	
IARC group	3

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Exposure may produce cough, mucous secretions, shortness of breath, chest tightness or other symptoms indicative of an allergic/sensitization reaction.

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: None known.

333 Stencil Filler

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General : Toxic to aquatic life.

1-Dodecanol (112-53-8)	
LC50 Fish 1	1.01 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	320 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	0.1855 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
ErC50 (Algae)	0.97 mg/l
NOEC Chronic Crustacea	0.014 mg/l (Exposure Time: 21 d - Species: Daphnia magna)
Ammonium hydroxide (1336-21-6)	
LC50 Fish 1	8.2 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
EC50 Daphnia 1	0.66 mg/l (Exposure time: 48 h - Species: water flea)
EC50 Daphnia 2	0.66 mg/l (Exposure time: 48 h - Species: Daphnia pulex)
NOEC Chronic Crustacea	3.47 mg/l
Ammonia (7664-41-7)	
LC50 Fish 1	0.44 mg/l (Exposure time: 96 h - Species: Cyprinus carpio)
EC50 Daphnia 1	25.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	0.26 - 4.6 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)
Thiram (137-26-8)	
LC50 Fish 1	0.0003 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static])
EC50 Daphnia 1	0.21 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	0.13 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)
NOEC (Acute)	225 mg/kg (Exposure time: 14 Days - Species: Eisenia foetida [soil dry weight])
NOEC Chronic Crustacea	0.008 mg/l (Daphnia magna (Water flea) - 21d exposure time)
NOEC Chronic Algae	0.0243 mg/l

12.2. Persistence and Degradability

333 Stencil Filler	
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

333 Stencil Filler	
Bioaccumulative Potential	Not established.
1-Dodecanol (112-53-8)	
Log Pow	5.36
Ammonia (7664-41-7)	
Log Pow	-1.14 (at 25 °C)
Thiram (137-26-8)	
BCF Fish 1	91
Log Pow	1.73 (at 20 °C)

12.4. Mobility in Soil No additional information available

12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste Treatment Methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, and international regulations.

Additional Information: Container may remain hazardous when empty. Continue to observe all precautions.

Ecology - Waste Materials: Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

333 Stencil Filler

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- 14.1. In Accordance with DOT** Not regulated for transport
14.2. In Accordance with IMDG Not regulated for transport
14.3. In Accordance with IATA Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

333 Stencil Filler	
SARA Section 311/312 Hazard Classes	Health hazard - Respiratory or skin sensitization
1-Dodecanol (112-53-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Ammonium hydroxide (1336-21-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
CERCLA RQ	1000 lb
Ammonia (7664-41-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on the United States SARA Section 302	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	100 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	500 lb
SARA Section 313 - Emission Reporting	1 % (includes anhydrous Ammonia and aqueous Ammonia from water dissociable Ammonium salts and other sources, 10% of total aqueous Ammonia is reportable under this listing)
Thiram (137-26-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	10 lb
SARA Section 313 - Emission Reporting	1 %

15.2. US State Regulations

Ammonium hydroxide (1336-21-6)	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
U.S. - Pennsylvania - RTK (Right to Know) List	
Ammonia (7664-41-7)	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
U.S. - Pennsylvania - RTK (Right to Know) List	
Thiram (137-26-8)	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
U.S. - Pennsylvania - RTK (Right to Know) List	

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision	: 10/24/2018
Other Information	: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

GHS Full Text Phrases:

Acute Tox. 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1

333 Stencil Filler

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Comb. Dust	Combustible Dust
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Gas 2	Flammable gases Category 2
Press. Gas (Comp.)	Gases under pressure Compressed gas
Resp. Sens. 1	Respiratory sensitization, Category 1
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization, Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H221	Flammable gas
H280	Contains gas under pressure; may explode if heated
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H334	May cause an allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)