

P248E

DOUBLE-COATED TISSUE DIFFERENTIAL ADHESION

DESCRIPTION

Black colored tissue coated on both sides with a solvent-based, pressure-sensitive acrylic adhesive for good initial tack and light proof bonding. One side (exposed) 'open' side provides moderately higher adhesion versus the 'closed' (liner) side.

Features a 5.0 mil easy release bleached kraft paper liner 74# (white).

Product is not repulpable.

PRODUCT APPLICATION

For splicing plastic film, paper, foil, etc. Also for the fastening of components like mirrors, tiles, nameplates, emblems and labels. For porous foam lamination used for heat breaking, gasketing and sealing.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 09/22

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Tissue
Adhesive	Solvent Acrylic
Loop Tack (oz/in of width)	77.6 (2.2kg/25mm)
Peel Adhesion (oz/in of width) PSTC-3	52.9 (1.5kg/25mm)
Total Thickness (mils)	4.3 (0.11mm) w/o liner
Shear Strength (hours) 1" x 1" x 1 kg @ 77°F (25°C) PSTC-7	>24
Service Temperature	-4°F to +176°F (-20°C to +80°C)
Color	Black

