

534

MEDIUM GRADE FLATBACK TAPE

DESCRIPTION

Considered by many as the “Industry Standard”, 534 is an aggressive pressure-sensitive flatback tape that has been specifically designed to offer a strong secure seal on a variety of substrates. This product is moisture resistant and performs well under a wide range of temperature and humidity conditions. 534 has an excellent balance between machine and cross direction tensile and tear strength in order to reduce failures in the field, specifically in medium duty splicing, tabbing and core starting applications. This product is not repulpable.

PRODUCT APPLICATIONS

Carton sealing, packaging, silk screening, picture framing, beaming/leasing, splicing, and tabbing.

GOVERNMENT COMPLIANCE

Approved as packaging tape by both U.S. Postal Service and U.P.S (United Parcel Service).
PPP-T-42C, Type II. C.I.D. A-A-883B, Type II.

STORAGE RECOMMENDATION

Store new stock behind current stock. Store in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F, and 40% to 50% relative humidity are recommended.

SHELF LIFE

When stored under recommended conditions, converted rolls have an expected shelf life of up to one (1) year from the date of shipment. Jumbo rolls have the same expected shelf life, but it is recommended that they are converted within six (6) months of date of shipment.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 04/18

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Kraft Flatback
Adhesive	Solvent Cast Natural / Synthetic Rubber
Adhesion to Steel (oz/in of width) PSTC-101	60 (16.4 N/25mm)
Tensile Strength (lbs/in of width) PSTC-131	42 (184 N/25mm)
Elongation (% at break)	7
Total Thickness (mils) PSTC-133	7.5 (0.19mm)
Operating Temperature Range	
Application	+50°F ~ +120°F (+10°C ~ +49°C)
Operating	+32°F ~ +200°F (0°C ~ +93°C)
Color	Brown

