

**FRU ELITE**

**DESCRIPTION**

NovaShield<sup>®</sup> FRU ELITE is a heavyweight fabric for applications requiring flame retardants and UV stability, such as membrane structures. This ELITE product is manufactured with a high strength film laminated to one side and a proprietary coating on the back side. This high strength film is used to enhance abrasion resistance, flex resistance, seam strength, UV resistance and longevity. The scrim is produced in a special weaving pattern to enhance flatness, abrasion resistance, and tear properties.

**FABRIC SPECIFICATIONS**

Weave: Woven HDPE scrim using natural FR/UV tapes  
 Coating: White flame retardant PE  
 Film: White flame retardant PE  
 Colour: White FRU only  
 Weight: 13.75 oz/yd<sup>2</sup> (466g/m<sup>2</sup>) +/- 5 %

**ROLL SPECIFICATIONS**

Cores: 4 inch I.D. or 5 inch I.D. available  
 Width: 144 inches (-0, +0.5)  
 Length: White/white – 500 yards

*These values are typical data and are not intended as limiting specifications.*



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA  
 Customer Service: 800.IPG.8273 | 800.474.8273  
 www.itape.com | info@itape.com

**PERFORMANCE PROPERTIES**

The following data are typical values based on ASTM standard tests. These data should not be considered a specification.

<b>Grab Tensile</b> ASTM D5034	Warp 430 lb 1909 N / Weft 400 lb 1776 N
<b>Strip Tensile</b> (N/5cm) ASTM D5035	Warp 265 lb/in (2353)/Weft 250 lb/in (2220)
<b>Tongue Tear</b> ASTM D2261	Warp 100 lb 444 N / Weft 90 lb 400 N
<b>Trapezoidal Tear</b> ASTM D4533	Warp 85 lb 377 N / Weft 85 lb 377 N
<b>Mullen Burst</b> ASTM D3786	665 psi / 4582 kPa
<b>Accelerated UV Weathering<sup>1</sup></b> ASTM G154	100% strength retention after 2000 hrs exposure @ 0.77 W/m <sup>2</sup> /nm, or 1200 hrs exposure @ 1.35 W/m <sup>2</sup> /nm
<b>Low Temperature Bend</b> ASTM D2136	-65°C

**FR PERFORMANCE**

This product meets the requirements of NFPA 701 – 2015 (Methods 1 and 2), ASTM E84 -16 (Class 1), CAN/ULC S102-10, CAN/ULC S109-14 (Small and Large Flame tests)

20-year Prorated Warranty – Please see your territory manager for details.

<sup>1</sup> Q.U.V [A-340 Lamps]; 8 hrs UV @ 60°C; 4hrs condensation @ 50°C

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 02/23

