

CONTRACTOR'S GRADE SHEATHING TAPE FOR BUILDING WRAP MATERIAL



DESCRIPTION

This tape is made of an UV resistant polypropylene and coated with high shear, high tack solvent based acrylic adhesive. This tape is meant for permanent application only. It will leave adhesive residue if removed.

MAIN FEATURES

- High tack adhesive provides aggressive contact
- Strong and durable holding power
- Water and moisture resistant
- Excellent resistance to UV and weathering
- Prevents air infiltration

APPLICATIONS

- Sealing of joints and seams of building wrap materials
- Tape has to be pressed firmly on surface
- Should be applied on clean, dry surfaces

TECHNICAL DATA

Backing.....	UV Resistant Polypropylene Film
Adhesive	Solvent Based Acrylic
Color.....	Blue with white print
Total Tape Thickness	3 mil
ASTM D1777	
Adhesion to Steel	40 oz/in
ASTM D-3330, Method A	
Tensile Strength at Break	30 lb/in
ASTM D3759, Method A	
Elongation at Break	120%
ASTM D3759, Method A	
Application Temperature Range	0°F to 122°F
Service Temperature Range	-40°F to 212°F
VOC (Volatile Organic Compound content)	Estimated 0.1%
Water Vapor Transmission	0.068 US perm
ASTM E96 Procedure A, Desiccant	
Water Penetration Rate.....	0.050 g/100 in ² /24 hr
ASTM D3816	
Air Permeance Rate	0.0002 cfm/ft ² @ 1.57 psf
ASTM E2178	

Please note:

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness.

The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded.

No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.